

Serial I/O(RS-232C) CF Card

CF60U



**Add Hi-Speed COM port
to your PDA, Palmtop PC**



Works as a standard COM port



► **Features**

- Add Hi-Speed COM port to your PDA, Palmtop PC.
- Works on Compaq iPAQ, Dell Axim, Toshiba Pocket PC, Fujitsu Pocket-LOOX, Casio and HP PDAs. (One free CF TypeII slot required.)
- Attach bar code scanners, magnetic stripe card readers, GPS receivers or other RS-232C devices.
- Supports modems, ISDN adaptors, instruments devices and biometric sensors.
- Easy to use, just Plug & Play. Works as a standard COM port on WindowsXP, Windows2000, WindowsMe, Windows98, Windows CE, Pocket PC 2000, Pocket PC 2002 and Handheld PC 2000.
- Bundled VB,VC sample source code and libraries allow you to make your own communication software.
- Ultra low power consumption allows a long battery life.
- Optional (not included) TypeII PC Card adapter allows to fit CF60U into a standard PC Card slots and use with Laptop PC.

► **System Requirements**

One free CF TypeII compatible slot.

OS

- WindowsXP, Windows2000, WindowsMe and Windows98/98SE.

Pocket PC 2000, Pocket PC 2002, Handheld PC 2000, WindowsCE 2.0 or later.

► **Certified PDA and USB devices**

PDA

Compaq : iPAQ with CF Jacket, PC Card Jacket.

Toshiba : Pocket PC e740

Dell : Axim

Casio : Casiopea

Fujitsu : Pocket Loox

RS-232C device

Analogue Modems, ISDN modems,

Bar code scanners, Magnetic stripe card readers, RF-ID tag readers,

Biometric sensors, Instrumental devices

► **Specifications**

Product name	Serial I/O(RS-232C) CF Card									
Product Number	CF60U									
Bus Interface	CF+ and Compact Flash Specification Rev.1.4 compliant									
Serial port interface	EIA/TIA-574 compliant									
Serial port Input/Output level	EIA/TIA-232 compatible (Output +/-5V, Input +/-15V to +/-5V)									
Serial Controller	16650 compatible UART									
Maximum Baud Rate	115,200 bps.									
Data format	Asynchronous, Start bit 1, Data bit 7/8, Parity bit Even/Odd/None, Stop bit 1/1.5/2.									
Serial Port Connector	9 pin D Shell male									
Physical Dimensions	CF TypeII 42.8(W) x 36.4(L) x 4.9(H) mm 1.69(W) x 1.43(L) x 0.13(H) inch									
Cable length	500mm (20 inch)									
Weights	CF Card : 10g. 0.35oz. Cable : 55g. 1.93oz.									
Power Consumption	<table border="1"> <thead> <tr> <th></th> <th>Standby</th> <th>Typical</th> </tr> </thead> <tbody> <tr> <td>5V Vcc</td> <td>1.2mA</td> <td>11.8mA</td> </tr> <tr> <td>3.3V Vcc</td> <td>2.2mA</td> <td>8mA</td> </tr> </tbody> </table>		Standby	Typical	5V Vcc	1.2mA	11.8mA	3.3V Vcc	2.2mA	8mA
	Standby	Typical								
5V Vcc	1.2mA	11.8mA								
3.3V Vcc	2.2mA	8mA								
OS Support	WindowsXP/2000/Me/98, WindowsCE, Pocket PC 2000, Pocket PC 2002, Handheld PC 2000.									
Certification	VCCI/FCC Part 15, Class B.									
Warranty	Removable Cable 90 days, Card 5 years.									
Package includes	<ul style="list-style-type: none"> • CF60U Serial I/O CF card • Removable cable. • Software CD-ROM < Software CD-ROM contents > -INF file for WindowsMe/98 -[Visual Basic/Visual C] Communication program sample source code. For Windows98/Me/2000/XP, WindowsCE, Pocket PC 2000, Pocket PC 2002, Handheld PC 2000. • User's Guide 									

* Covered and licensed by U.S. Patents 4,603,320 4,686,506 4,972,470.